



Bush Hog's Famous Reliability In A Special Duty Cutter

Designed for smaller tractors, the new Bush Hog® 2212 Flex Wing Rotary Cutters are ideal for rolling, uneven terrain and orchards. They are built with Bush Hog TOUGH Features so they will deliver superior performance the first day on the job and for years to come.



Bush Hog® TOUGH 2212 Flex Wing Rotary Cutter For 50 to 75 PTO HP Tractors

BUSH HOG® TOUGH FEATURES

TOUGH Driveline Retaining Ring

TOUGH Heavy Duty Axle Turn Buckles
TOUGH Greaseable Axle Pivot Points With
Spring Steel Bushings For Extended Wear
TOUGH Dual Spring Shock Absorption



MODEL	2212
Cutting Width	12 ft
Cutting Capacity	1 1/2 inch diameter
Cutting Height	2 to 14 inches
Overall Width and Length (from Clevis to Wheel Hub at	Transport Height) 12 ft 8 inches x 13 ft 3 inch
Transport Width (from wing skid to wing skid)	5 ft 8 inches
Tractor PTO	540 RPM
Minimum Tractor HP	50 PTO
Deck Thickness	10 gauge
Side Bands	7 gauge x 12 inches
Gearbox HP	160 -Transfer, 75 - Center, 75 - Wings
PTO Driveline	ASAE Cat. 4 (540 RPM)
Wing Driveline	ASAE Cat. 3
Slip Clutches	(3) Multiple Plate Clutches
Blade Tip Speed	15,604 FPM
Blades	1/2 x 4 inch Uplift with 6 inch Overlap
Type Hitch	Self Leveling with Swivel Clevis
Wing Flex (Operating)	87° Up to 22° Down
Tires	Choice of Laminated Tire, Used Aircraft Tire, or Pneumatic 15 inch Wheel
Axles	Greaseable pivot points with bushings
Wheel Shock Protection	Springs on Center Section
Deflectors	Banding and Belting; Chains Optional
Options	Chain Shielding, Valve & Stand Kit
Warranty 1	year limited warranty with a 5 year gearbox limited warranty

Driveline safety retaining rings




Turn Buckles



Pivot Points



Dual Spring Shocks



Driveline Retaining Ring

Dealer Info:

BUSH HOG EXCLUSIVE:

